



RTS 5 3/2

Ø	-0,3	0,3-0,5	0,5-0,9	0,9-1,5	1,5-3,0	3,0-5,0	5,0-7,0	7,0-9,0
TYPE	RTS	RTS	RTS	RTS	RTS	RTS	RTS	RTS
	5-0,3 3/2	5-0,5 3/2	5-0,9 3/2	5-1,5 3/2	5-3,0 3/2	5-5,0 3/2	5-7,0 3/2	5-9,0 3/2
A	63	89,5	99	138	146	185	250	275
B/B1	45/12	62/20	73/20	102/22	110/27	140/35	190/45	210/50
C	33	35	40	51	51	60	70	70
D	4	7	17	23	31	40	52	62
E	4	5	6	6	6	8,5	12	12
F	42	52	76	107	123	143	276	316
G	12	15	15	20	20	20	25	25
H	17	24	28	44	48	58	83	94
K	25	45	53	82	90	114	150	170
L	50	62	88	119	135	160	300	340
M	4,5	4,5	5,5	6,6	6,6	9	11	13,5
N	13,8	17,5	19	24,5	28	30	37	37
O		17	20	20	20	26	40	40
P	6	7,5	7,5	10	10	10	12,5	12,5
S	M4	M5	M6	M8	M8	M8	M12	M12
T	5	6	6	8	8	8,5	15	15
SW1/SW2	3/7	4/10	5/12	8/13	8/13	8/19	10/24	10/24
kg	0,2	0,5	0,9	2,0	2,7	4,7	13,2	16
WR	4	7	17	23	31	40	520	62
F [N]	2	3	6	20	157	314	550	687

Richtapparat mit einzeln verstellbaren Rollen und Schnellverschluß
Dresseur avec des galets réglables séparément et fermeture rapide
Straightener with separately adjustable rollers and quick-closing

