



## RT 5 3/2

Ø -0,3 0,3-0,5 0,5-0,9 0,9-1,5 1,5-3,0 3,0-5,0 5,0-7,0 7,0-9,0

TYPE	RT 5-0,3 3/2	RT 5-0,5 3/2	RT 5-0,9 3/2	RT 5-1,5 3/2	RT 5-3,0 3/2	RT 5-5,0 3/2	RT 5-7,0 3/2	RT 5-9,0 3/2
A	51	69,5	82	116	124	154	206	226
B	45	62	73	102	110	140	190	210
C	15,8	21	24,3	33,3	41,4	44,1	59,8	54
D	4	7	17	23	31	40	52	62
E	4	5	6	6	6	8,5	12	12
F	42	52	76	107	123	143	276	316
G	12	15	15	20	20	20	25	25
H	17	24	28	44	48	58	83	94
K	25	45	53	82	90	114	150	170
L	50	62	88	119	135	160	300	340
M	4,5	4,5	5,5	6,6	6,6	9	11	13,5
N	13,8	17,5	19	24,5	28	30	37	37
O		17	20	20	20	26	40	40
P	6	7,5	7,5	10	10	10	12,5	12,5
S	M4	M5	M6	M8	M8	M8	M12	M12
T	5	6	6	8	8	8,5	15	15
SW1	3	4	5	8	8	8	10	10

kg 0,1 0,2 0,4 1,2 1,7 2,9 8,2 10

WR 4 7 17 23 31 40 520 62

F [N] 2 3 6 20 157 314 550 687

Richtapparat mit einzeln verstellbaren Rollen  
Dresseur avec des galets réglables séparément  
Straightener with separately adjustable rollers

