



## RT 7 3/4

Ø -0,3 0,3-0,5 0,5-0,9 0,9-1,5 1,5-3,0 3,0-5,0 5,0-7,0 7,0-9,0

TYPE	RT 7-0,3 3/4	RT 7-0,5 3/4	RT 7-0,9 3/4	RT 7-1,5 3/4	RT 7-3,0 3/4	RT 7-5,0 3/4	RT 7-7,0 3/4	RT 7-9,0 3/4
A	51	69,5	82	116	124	154	206	226
B	45	62	73	102	110	140	190	210
C	15,8	21	24,3	33,3	41,4	44,1	59,8	54
D	4	7	17	23	31	40	52	62
E	4	5	6	6	6	8,5	12	12
F	54	68	100	143	167	193	376	436
G	12	15	15	20	20	20	25	25
H	17	24	28	44	48	58	83	94
K	25	45	53	82	90	114	150	170
L	62	78	112	155	179	210	400	460
M	4,5	4,5	5,5	6,6	6,6	9	11	13,5
N	13,8	17,5	19	24,5	28	30	37	37
O		17	20	20	20	26	40	40
P	6	7,5	7,5	10	10	10	12,5	12,5
S	M4	M5	M6	M8	M8	M8	M12	M12
T	5	6	6	8	8	8,5	15	15
SW1	3	4	5	8	8	8	10	10

kg 0,1 0,2 0,5 1,6 2,3 3,8 11,2 13,7

WR 4 7 17 23 31 40 520 62

F [N] 10 12 25 59 353 569 951 1374

**Richtapparat mit einzeln verstellbaren Rollen**  
**Dresseur avec des galets réglables séparément**  
**Straightener with separately adjustable rollers**

